

Octo Water Treatment



Polywound Filters

Octo Water Treatment Polywound cartridges are manufactured from a durable polypropylene cord that is wound around a rigid polypropylene core. They are an economical solution to particles ranging from silt, sand, rust etc.

suitable for a wide range of chemical and temperature applications, suitable for potable water, food, process water, chemical, photographic, electronic etc.

Available in 5", 9 3/4", 10", 20", 30" and 40" with filtration depths from 1µ to 200µ.

Order Codes

Standard 2 1/2" Diameter Cartridges

Length 9 = 9 3/4"
 PW = Polywound Micron = 5µ

PW	9	05
PW	20	25

= Polywound 20" x 2 1/2" 25µ

4 1/2" Diameter Cartridges

BB = Width 4 1/2"
 PW = Polywound Length 20 = 20"
 Micron = 5µ

PW	BB	20	05
PW	BB	09	50

= Polywound 9 3/4" x 4 1/2" 50µ

Caution: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



Octo Marine SAS
 10 Cite Artisanale de Valbonne, 108 Chemin de Saint Helene,
 Valbonne, 06560, France
 Email- info@octomarine.net - Web- <http://www.octomarine.net>

